



REDBOX
INTERNATIONAL

RB75A

MODEL **RB75A**

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES

NATO S/N 2995-99-305-9056



SUPPLIED WITH UNIT

Charger
Output Cable

OPTIONAL EXTRAS

Thermal Protection Bag
Various output cable lengths
Croc Clips
Various Connectors
Ramp Trolley
25A, 50A, 75A or 100A 28V DC power supply

RB75A 24V	
Max amps	1700 (Nom. short circuit current) 2600 (Max. short circuit current)
Capacity	38 Amp Hrs @ 10 hr rate
Max Voltage	26V DC
Size (cm)	L 45 x W 10 x H 38
Weight kg	29
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft connector
Charger	8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

- *Totally weather protected.*
- *Air transportable, 'Non Hazardous'*
- *Maintenance free.*
- *Tough and compact.*
- *No memory effect.*
- *Works in any orientation.*
- *High charge retention.*
- *Long shelf life.*
- *Fast recharge.*
- *External charger for prolonged unit life.*
- *No cycling.*
- *Leak proof.*
- *Cells replaceable on condition.*
- *Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.*
- *Starts Main Battle Tanks.*
- *Starts Armoured Fighting Vehicles.*
- *Lightweight portable start power at remote locations.*

