

MODEL **TC**400A-28

HIGH CAPACITY, MULTIPLE START POWER UNIT FOR AIRCRAFT

(NSN 2995-99-807-1213)

SUPPLIED WITH UNIT
Charger
Output Cable

Max Amps	3500A (Nom. short circut current) 5200A (Max. short circuit current)
Capacity	115 Amp Hrs
Max Voltage	30.3V DC
Size (cm)	L 78 x W 35 x H 30
Weight kg	140 - 165
Operating Temp.	-40°C - +60°C
Case	Zinc coated steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	3m heavy duty cable with aircraft connector
Charger	20A Electronic110/230v. Charging time less than 2 hours from 50%.

TC400A-28

Specification may change without notice

- Totally weather protected.
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- · No memory effect.
- · High charge retention.
- Long shelf life.
- Fast recharge.
- External charger for prolonged unit life.
- No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- Portable start power at
- remote locations.

f t in

www.redboxint.com sales@redboxint.com Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848

OPTIONAL EXTRAS	
Towbar	
Handlebar and Casters	
Various Output Cable Lengths	
Various Connectors	